

KENT 上海垦特实业有限公司

上海垦特实业有限公司

专业流体控制产品供应商





M8塑封出线式

Connector M8

Pre-wired

DIN IEC 61076-2-104

Number of contacts	3 / 4
Rated voltage	3-pol: 60 V 4-pol: 30 V
Operating current	4 A
PVC/PUR-cable	0,25 mm²
Cable diameter	4-5 mm
Protection class	IP 67
Housing material	PUR
Contact material	Cu Sn / Au / Ni
Gasket	NBR
Screw	Cu Zn (Ni)
Temperature range	-25° C ... +80° C





1:Brown
2:White
3:Blue
4:Black



Type: straight or 90°	Male	Male	Male	Female	Female	Female
	2m	5m	10m	2m	5m	10m
straight / PUR 3x0,25	K083S01R02	K083S01R05	K083S01R10	K083R01R02	K083R01R05	K083R01R10
straight / PUR 4x0,25	K084S01R02	K084S01R05	K084S01R10	K084R01R02	K084R01R05	K084R01R10
90° / PUR 3x0,25	K083S02R02	K083S02R05	K083S02R10	K083R02R02	K083R02R05	K083R02R10
90° / PUR 4x0,25	K084S02R02	K084S02R05	K084S02R10	K084R02R02	K084R02R05	K084R02R10

Number of contacts	3 / 4
Rated voltage	3-pol: 60 V 4-pol: 30 V
Operating current	4 A
Cable diameter	3,5-5 mm
Termination	solder
Protection class	IP 67
Housing material	PA
Contact material	Cu Zn / Cu Sn / Au / Ni
Gasket	NBR
Screw	Cu Zn (Ni)
Temperature range	-40° C ... +80° C



1:Brown
2:White
3:Blue
4:Black


Type: straight

Male

Female

straight / 3-pol.	T083S01P7	T083R01P7
straight / 4-pol.	T084S01P7	T084R01P7

Number of contacts	4 / 5
Rated voltage	4-pol: 250 VAC / 300 VDC 5-pol: 60 VAC / 60 VDC
Operating current	4 A
PVC/PUR-cable	0,34 mm ²
Cable diameter	5 mm
Protection class	IP67
Housing material	PUR
Contact material	Cu Sn / Au / Ni
Gasket	NBR
Screw	Cu Zn (Ni)
Temperature range	-25° C ... +80° C



1:Brown
2:White
3:Blue
4:Black
5:Grey



Type: straight or 90°	Male	Male	Male	Female	Female	Female
	2m	5m	10m	2m	5m	10m
straight / PUR 4x0,34	K124S01R02	K124S01R05	K124S01R10	K124R01R02	K124R01R05	K124R01R10
straight / PUR 5x0,34	K125S01R02	K125S01R05	K125S01R10	K125R01R02	K125R01R05	K125R01R10
90° / PUR 4x0,34	K124S02R02	K124S02R05	K124S02R10	K124R02R02	K124R02R05	K124R02R10
90° / PUR 5x0,34	K125S02R02	K125S02R05	K125S02R10	K125R02R02	K125R02R05	K125R02R10

Number of contacts	8
Rated voltage	30 VAC / 36 VDC
Operating current	3 A
PVC/PUR-cable	0,25 mm ²
Cable diameter	6-7mm
Protection class	IP 67
Housing material	PUR
Contact material	Cu Sn / Au / Ni
Gasket	NBR
Screw	Cu Zn (Ni)
Temperature range	-25° C ... +80° C




Type: straight or 90°	Male	Male	Male	Female	Female	Female
	2m	5m	10m	2m	5m	10m
straight / PUR 8x0,25	K128S01R02	K128S01R05	K128S01R10	K128R01R02	K128R01R05	K128R01R10
90° / PUR 8x0,25	K128S02R02	K128S02R05	K128S02R10	K128R02R02	K128R02R05	K128R02R10

Connector M 12

Pre-wired with LED

DIN IEC 61076-2-101


Number of contacts	3
Rated voltage	10-30 VDC
Operating current	4 A
PUR-cable	0,34 mm²
Cable diameter	5 mm
Protection class	IP67
Housing material	PUR
Contact material	CuSn/Au/Ni
Gasket	NBR
Screw	Cu Zn (Ni)
Temperature range	-25° C ... +80° C



- 1:Brown
- 2:White
- 3:Blue
- 4:Black
- 5:Grey




NPN



circuit 1

PNP



circuit 2

	Female	Female	Female	Special Feature	
	2 m	5 m	10 m		
PUR 3x0,34 / 2x LED	K123R0R02A1	K123R01R05A1	K123R01R10A1	circuit 1 NPN	straight
PUR 3x0,34 / 2x LED	K123R02R02A1	K123R02R05A1	K123R02R10A1	circuit 1	90°
PUR 4x0,34 / 2x LED	K123R01R02A2	K123R01R05A2	K123R01R10A2	circuit 2	straight
PUR 4x0,34 / 2x LED	K123R02R02A2	K123R02R05A2	K123R02R10A2	PNP circuit 2	90°


M12组装式

Connector M 12

Field attachable

DIN IEC 61076-2-101

Number of contacts	4 / 5/8
Rated voltage	4-pol: 250 VAC / 300 VDC 5/8 pol: 60 VAC / 60 VDC
Operating current	4 A
Cable diameter	PG 7: 2,5-6,5 mm PG 9: 3,5-8,0 mm
Termination	screws
Protection class	IP 67
Housing material	PA
Contact material	Cu Zn / Cu Sn / Ni
Gasket	NBR
Screw	Cu Zn (Ni)
Temperature range	-25° C ... +80° C




Type: straight or 90°	Male	Male	Female	Female
	PG 7	PG 9	PG 7	PG 9
straight / 4-pol.	T124S01P7	T124S01P9	T124R01P7	T124R01P9
90° / 4-pol.	T124S02P7	T124S02P9	T124R02P7	T124R02P9
straight / 5-pol.	T125S01P7	T125S01P9	T125R01P7	T125R01P9
90° / 5-pol.	T125S02P7	T125S02P9	T125R02P7	T125R02P9
straight / 8-pol.	T128S01P7	T128S01P9	T128R01P7	T128R01P9
90° / 8-pol.	T128S02P7	T128S02P9	T128R02P7	T125R02P9



Connector M 12
Male chassis connector

DIN IEC 61076-2-101

Number of contacts	4 / 5 / 8
Rated voltage	4 - pol: 250 VAC / 300 VDC 5 / 8 - pol: 60 VAC / 60 VDC
Operating current	4 / 5 - pol: 4 A 8 - pol: 3 A
PVC - cable	4 / 5 - pol: 0,34 mm² 8 - pol: 0,25 mm²
Cable diameter	2 mm
Protection class	IP 67
Housing material	Cu Zn / Ni
Contact material	Cu Sn / Au / Ni
Gasket	NBR
Screw	Cu Zn (Ni)
Temperature range	-25° C ... +80° C



- 1:Brown
- 2:White
- 3:Bule
- 4:Black
- 5:Grey




Type	Male	Male	Male	Male	Male	Male
	PG 9 / 4 - pol	PG 9 / 5 - pol	PG 9 / 8 - pol	M 16 / 4 - pol	M 16 / 5 - pol	M 16 / 8 - pol
front mounting	850461T	850561T	850861T	850462T	850562T	850862T
back mounting	850471T	850571T	850871T			
for printed circuits	850481T	850581T	850881T	850482T	850582T	850882T
fixing nut	850001T(PG 9)	850001T(PG 9)	850001T(PG 9)	850002T(M 16)	850002T(M 16)	850002T(M 16)

Connector M 12
Male chassis connector

DIN IEC 61076-2-101

Number of contacts	4 / 5 / 8
Rated voltage	4 - pol: 250 VAC / 300 VDC 5 / 8 - pol: 60 VAC / 60 VDC
Operating current	4 / 5 - pol: 4 A 8 - pol: 3 A
PVC - cable	4 / 5 - pol: 0,34 mm ² 8 - pol: 0,25 mm ²
Cable diameter	2 mm
Protection class	IP 67
Housing material	Cu Zn / Ni
Contact material	Cu Sn / Au / Ni
Gasket	NBR
Screw	Cu Zn (Ni)
Temperature range	-25° C ... +80° C



- 1:Brown
- 2:White
- 3:Bule
- 4:Black
- 5:Grey



Type	Female	Female	Female
	PG 9 / 4 - pol	PG 9 / 5 - pol	PG 9 / 8 - pol
front mounting	851461T	851561T	851861T
back mounting	851471T	851571T	851871T
for printed circuits	851481T	851581T	851881T
fixing nut	850001 T(PG9)	850001T (PG9)	850001T(PG9)

KANT
Druckschalter GmbH

压力开关 真空开关



压力继电器 液压阀



压力传感器 压力开关
液位 流量 温度传感器



压力 温度 流量开关
光电传感器 接近开关



压力 温度 流量
开关 传感器



压力 温度开关
蓄能器



DIN43650插头 工业连接器
传感器分线盒



电子-液压



DIN仪表插头
工业连接器



压力 温度 流量 液位
开关 传感器



水阀 定时器



DIN43650插头
压力开关 传感器



流量开关 流量计 水阀



压力传感器



球阀 液压阀



CONTROL PRODUCTS

压力 温度 流量 液位
开关 传感器



防爆液位开关

上海垦特实业有限公司

电话 : 021-36374188 51292285

传真 : 021-51062637 36376232

网站 : [Http://www.shkente.cn](http://www.shkente.cn)

邮箱 : shkente@126.com

服务热线 : 18917054460